

Competition Rules:

1. Any street stock passenger automobile may be used. NO pickups, 4x4's, compacts, or imports allowed. A minimum wheel base of 102". Exceptions to stock are listed below:
 - a. All doors and trunk lids must be bolted, welded, or strapped shut. Leave a 6"x6" minimum inspection hole in the trunk so we can look inside. You will not be allowed to race without a hood or trunk lid.
 - b. Only 1 battery allowed. Battery must be located under the hood and mounted securely. No tarp straps. No firewall cutouts permitted.
 - c. Any DOT street tires and any O.E. M. or standard aftermarket rims may be used.
2. OEM gas tanks must be in stock position and held securely with 2 additional straps made from 1/8"x 1 1/2" wide strap iron (minimum) must be welded or bolted with 3/8 bolts and adequate washers. Only one gas tank allowed. You may replace your gas tank with approved racing fuel cell with steel outside container, and place it under the trunk lid between the frame rails. Any gas leaks and you are disqualified. *Allowed to repair per track official.*
3. No reinforcement of car frame, structure, or bumpers allowed except for those listed below:
 - a. Front and rear bumpers must be welded or strapped to the frame so they won't fall off if impacted. 1/8" sheeting allowed from bumper to fender. If your bumper falls off you will be disqualified and out of the race. Must be original type bumper. No chopped off or shortened bumpers permitted.
 - b. Optional braces from frame to corners of front and rear bumpers. Braces not to be made of more than 1 5/8" O.D. pipe. One brace per corner. (See illustration # 2) **NO NERF BARS.**
 - c. Rear frame of car may be reinforced to protect gas tank or fuel cell, but it must stop 3" from the top of the arch in frame above rear axle and ahead of the rear bumper (See illustrations # 4 and # 5) Reinforcement must also stay between frame rails.
 - d. Optional hoop over radiator with 2 support braces, neither to exceed 1 5/8" O.D. pipe. Hoop must not exceed 2" in front of the radiator mount. Braces not to extend past front of A frames. (See illustration # 3) One brace made of 1 5/8" O.D. pipe maximum may be added between front frames. (See illustration # 2A)
 - e. Metal used to cover radiator or front of car must not exceed 1/8" with no bracing. Skid plate allowed, made of 1/8" sheeting maximum, from radiator saddle to front cross member.
 - f. You will be allowed to repair damaged area of car, but repairs must not extend beyond damaged area and must not be considered excessive. Excessive sheeting of body will not be allowed. Call for official suggestions and approval.
4. No metal removed from car (except chrome trim and glass frames). Wheel wells and fender liners, etc. can be altered 2" to 3".
5. No suspension alterations permitted. All suspension parts must be stock appearing and in stock position. No coil over shocks. No racing springs.
6. Absolutely no glass allowed left in car or inside doors. Broken glass must be completely cleaned out of the car before it comes to the track.
7. All trim, light bezels, door handles, chrome, etc. must be removed completely.
8. All debris and loose materials must be removed from the car and trunk. Back seats must be replaced with tin flash shield between driver and rear of the car.
9. No exhaust coming out of the hood. No holes allowed in hood.
10. No water bars or tanks. No lead weights, sandbags, or other weight can be added to the car.
11. Cars must have working brakes and brake light in rear window. Light must be 3" across.
12. No profanity on cars.